

Flexible Current Probe Meter

APPA sFlex-10T/18T Clamp meter



Features:

- 3000A AC current measurement
- Slide switch to change range
- Voltage output to universal voltage meters
- 10/18inch head cable length
- 7.5mm coil diameter for tight space measurement
- 2 meter extension cable
- Low Batt. LED indicator
- Ergonomically designed one hand operation
- CAT IV 600V/ CAT III 1000V safety standard

Specification:(All at 23°C±5°C < 80%RH)

Measuring Range: 30A

Output Sensitivity: 100mV/A

Basic accuracy: ±1% of full scale

Measuring Range: 300A

Output Sensitivity: 10mV/A

Basic accuracy: ±1% of full scale

Measuring Range: 3000A

Output Sensitivity: 1mV/A

Basic accuracy: ±1% of full scale

Frequency Range: 45Hz~500Hz

Operating Temperature: 0°C ~50°C

Storage Temperature: -20°C ~60°C

Temperature Coefficient: 0.2 x (Spec. Accuracy)/°C,
< 18°C, > 28°C

Safety: Designed to meet IEC61010-1

Battery Life: 100 hours (ALKALINE)

Power Requirement: IEC LR03, AM4 or AAA size 1.5V x 2pcs

Dimensions:

sFlex-10T: 130mm(W) x 270mm(L) x 27mm(D)

sFlex-18T: 178mm(W) x 351mm(L) x 27mm(D)

Weight: Approx. 200g

Specification subject to change without notice

APPA TECHNOLOGY CORP.

9F, 119-1 Pao-Zong Rd., Shin-Tien

Taipei 231, Taiwan. R.O.C.

Tel:+886-2-29178820

Fax:+886-2-29170848

E-mail:info@appatech.com

<http://www.appatech.com>

ISO 9001 CERTIFIED